

WO2005029435

Title:

**METHOD AND APPARATUS FOR DETERMINING OPERATIONAL CONDITION
OF POLLUTION MONITORING EQUIPMENT**

Abstract:

A method for determining an operational condition of a particle detection system, the particle detection system comprising at least one sample inlet for receiving a sample flow from a monitored region, the method comprising the step of: conducting an upstream measurement of a flow rate through the at least one sample inlet.

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number
WO 2005/029435 A1

(51) International Patent Classification⁷: **G08B 29/12**,
29/00, G01F 1/00

(21) International Application Number:
PCT/AU2004/001320

(22) International Filing Date:
24 September 2004 (24.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003905197 24 September 2003 (24.09.2003) AU

(71) Applicant (for all designated States except US): **VISION
FIRE & SECURITY PTY LTD** [AU/AU]; 495 Blackburn
Road, Mount Waverley, Victoria 3149 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KNOX, Ron** [AU/AU];
90 Allison Road, Mount Eliza, Victoria 3930 (AU).

(74) Agents: **HENSHAW, Damon et al.**; 1 Nicholson Street,
Melbourne, Victoria 3000 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR DETERMINING OPERATIONAL CONDITION OF POLLUTION MONITOR-
ING EQUIPMENT



(57) Abstract: A method for determining an operational condition of a particle detection system, the particle detection system comprising at least one sample inlet for receiving a sample flow from a monitored region, the method comprising the step of: conducting an upstream measurement of a flow rate through the at least one sample inlet.